



RoomWrap

A classic calendered adhesive-backed PVC film with a grey back.

RoomWrap is designed for smooth or slightly textured floors and walls, doors, glass and tile.

APPLICATIONS

- Wall Murals
- Short-term POP Campaigns
- Floor Graphics (pair with ProtectWalk Non-Skid Laminate)

RoomWrap

MATERIAL

Face Film	Smooth White PVC with a Gloss Finish
Back Side	Grey Adhesive
Adhesive	Grey Removable Solvent Acrylic (20 g/m ² +/- 3g/m ²)
Liner	White Siliconized Paper - 120g/m ²
Film Thickness	4 mil (100μ +/-5μ)
FR Certification	ASTM E84, B1

DURABILITY

Interior	Up to 1 Year
Exterior	Short-Term, Dependent on Application
Environment	Humidity & Solvent Resistance – Good
Shelf Life	1 Year
Storage Requirements	Store at +59°F to +75°F (+15°C to +24°C) and Relative Humidity Between 40% and 65%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Removability	Cleanly Removable with no Adhesive Residue up to 6 Months – Adhesion May Increase over Time
Removal Temp	+50°F (+10°C) or Greater

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean installation surface with a mild detergent and water and dry thoroughly. ALWAYS clean and dry glass surface prior to application.

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Digital - Solvent, Eco-Solvent, Latex & UV
- Screen Print



Material Sizes

- 54" x 150'



Advantages

- Match with ProtectWalk or UltraProtection Laminate for a Complete Interior Floor Graphic Solution
- Cleanly Removable for Up to 6 Months – No Residue
- Good Heat Resistance, Dimensional Stability, and Chemical Resistance

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.
1-704-872-2216 • www.cgxusa.com