



panoRama Cast Laminate

An optically clear cast PVC laminate with a gloss finish, backed with clear permanent adhesive.

Enhance the durability and longevity of perforated window film and other print media, preserving clarity for up to 10 years.

APPLICATIONS

- Transit, Vehicle, and Fleet Graphics
- Perforated Window Graphics
- Long-Term Outdoor Signage

panoRama Cast Laminate

MATERIAL

Face Film	Optically Clear Cast PVC with a Gloss Finish
Back Side	Clear Adhesive
Adhesive	Permanent Solvent
Liner	PET - 1.5 mil (38µ +/- 5µ)
Film Thickness	2 mil (190µ +/- 5µ)
FR Certification	Not Tested
Recyclable	No

DURABILITY

Exterior	Up to 10 Years - Vertical Exposure under North American Midwestern Conditions
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	2 Years with Proper Storage
Storage Requirements	Store at +68°F to +78°F (+10°C to +24°C) and Relative Humidity Between 45% and 55%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (-4°C)
Service Temp	-50°F to +225°F (-17°C to +121°C)
Removability	N/A

Surface must be clean and dry. Handle film with care to prevent damage, fingerprints, debris, and contaminants that could become apparent on the finished product. A roll or table laminator is recommended for best application and finish. Prevent contact with solvents or ammonia-based cleaners. For best results, clean final installation surface with soap and water ONLY. Rinse with water and dry after cleaning. ALWAYS clean and dry glass surface prior application.

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Generally Not Used for Printing



Material Sizes

- 54" x 164'
- 60" x 164'



Advantages

- Cast Construction Offers Conformability and Long-Lasting Protection to Printed Media
- The Film's Optical Clarity Won't Cloud or Otherwise Detract from Branding and Messaging, Especially on Window Applications
- Stabilizes and Prolongs the Exterior Durability of Window and Print Films

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

704-872-2216 • www.cgxusa.com