



panoRama Green Laminate

A gloss, optically clear polyester laminate.

Add robust durability, resilience, and protection, especially to window graphics.

Recyclable when layered over another PET film such as panoRama Green.

APPLICATIONS

- Perforated Window Film Protection
- Any Environment Where Optical Clarity and Graphic Protection are a Priority.

panoRama Green Laminate

MATERIAL

Face Film	Optically Clear Gloss Polyester
Back Side	Clear Adhesive
Adhesive	Clear Permanent Acrylic
Typical Adhesion Values	Stainless Steel: 2.7lb/in (24 hr. Dwell Time)
180° Peel Test	
Liner	Clear Polyester - 1.2 mil
Film Thickness	1 mil
Gloss Level	125 (avg.) @ 60°

DURABILITY

Exterior	Up to 2 Years
Shelf Life	1 Year
Storage Requirements	Store at 70°F (+ 21°C) and Relative Humidity of 50%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (+10°C)
Service Temp	-65°F to +225°F (-54°C to +107°C)
Laminating Method	Cold

CHEMICAL RESISTANCE

Non-continuous Immersion	<ul style="list-style-type: none"> • Water • Detergent • Distilled Water 	<ul style="list-style-type: none"> • Ammonium Hydroxide - 10% • Gasoline • Hydrochloric Acid - 10%
--------------------------	---	---

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. Printed material must be completely dry and/or off-gassed prior to lamination.

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Not Applicable



Material Sizes

- 54" x 100'



Advantages

- Will Not Shrink or Expand - Extremely Dimensionally Stable
- Helps Prevent Tunneling or Channeling
- Provides Outstanding Resistance to Marking and Scuffing

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

1-704-872-2216 • www.cgxusa.com