

# panoRama Tape

## MATERIAL

Face Film	Optically Clear Polyester
Adhesive Inside	Permanent Clear Acrylic - 1 mil (25µ +/-10µ)
Adhesive Outside	Semi-Permanent Clear Acrylic - .75 mil (19µ +/-10µ)
Liner	Removable Polyester - 1 mil (24µ +/-10µ)
Film Thickness	2 mil (50µ +/-10µ)
FR Certification	Not Tested

## DURABILITY

Interior	Up to 1 Year
Exterior	Not Recommended
Environment	Humidity & Solvent Resistance - Good (Indoor Applications Only)
Shelf Life	1 Year
Storage Requirements	Store at +59°F to +68°F (+15°C to +20°C) with a Relative Humidity between 45% to 65%
Repositionable	Yes

## APPLICATION/REMOVAL

Application Temp	+50°F to +86°F (+10°C to +30°C)
Service Temp	0°F to +122°F (-17°C to +50°C)
Removability	Clean Removal with No Adhesive Residue, up to 6 Months - Adhesion May Increase over Time
Removal Temp	+50°F (+10°C) or Greater
Exclusions	NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. For full installation & removal instructions, please refer to "panoRama Film8020 Application Recommendations."

\*For critical substrates and all surfaces, please test PRIOR to application.



### Printing Methods

- Not applicable



### Material Sizes

- 1" x 200'



### Advantages

- Makes Installing Interior Window Graphics Easy - No Professional Installer Needed
- Install Window Graphics Any Time of Year
- Keep Window Graphics Safely on the Inside for Less Vandalism
- Designed for Use with panoRama Film8020 and panoRama Film7030

### → For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

**1-704-872-2216 • www.cgxusa.com**