



panoRama Clear8020, 7030

A clear, inside mount, self-adhesive perforated window film.

Especially designed for interior applications where city ordinances, tenant agreements, or inclement weather prevent exterior mount window signage.

Available in 80/20 and 70/30 film/open ratios.

APPLICATIONS

- Retail Windows - POP
- Building Wraps
- Rear or Side Bus Windows
- Rear Car Windows
- All Interior Window or Glass Applications

panoRama Clear8020, 7030

MATERIAL

| | |
|------------------|---|
| Face Film | Printable Clear Gloss Perforated PVC |
| Back Side | Clear |
| Adhesive | Removable Semi-Permanent Clear |
| Liner | Paper/Polyester Double Liner – 2 mil (50µ +/-10µ) |
| Film Thickness | 6 mil (150µ +/-10µ) |
| Hole Diameter | 1.5 mm |
| FR Certification | Not Tested |

DURABILITY

| | |
|----------------------|---|
| Interior | Up to 2 years – Vertical Exposure under Normal Conditions |
| Exterior | Not Applicable |
| Environment | Humidity & Solvent Resistance – Good |
| Shelf Life | 1 Year |
| Storage Requirements | Store at 59°F to 68°F (+15°C to +20°C) and Relative Humidity between 45% to 65% |
| Repositionable | No |

APPLICATION/REMOVAL

| | |
|--------------------|--|
| Application Temp | +50°F to +86°F (+10°C to +30°C) |
| Service Temp | +0°F to +122°F (-17°C to +50°C) |
| Removability | Clean Removal with No Adhesive Residue, up to 6 Months – Adhesion May Increase over Time |
| Removal Temp | +50°F (+10°C) or Greater |
| Exclusions | +50°F (+10°C) or Greater |
| Application Advice | NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available) |

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. For full installation & removal instructions, please refer to "panoRama Clear Perforated Window Film Application & Removal Guide".

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Digital – UV with White Ink
- Screen Print – Solvent and UV (White Ink Needed)



Material Sizes

- 54" x 100'



Advantages

- NO Lamination Needed – Window Protects the Graphic
- Easy Install on Inside Avoiding Inclement Weather Conditions or Costly Install Equipment
- Available in 80/20 and 70/30 Film/Open Ratios

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

704-872-2216 • www.cgxusa.com