



UltraProtection Laminate

A textured PVC laminate designed for medium- to long-term graphics protection.

Add robust durability, resilience, and protection to any graphics.

The glossy textured surface is slip resistant – ideal for use in busy environments to build brand awareness or communicate your message.

APPLICATIONS

- Long-term Wall Murals
- Museum Exhibits
- High-Traffic Event Graphics
- Showrooms
- Floor Mats
- Counter Mats

UltraProtection Laminate

MATERIAL

Face Film	Textured, Transparent PVC Film
Back Side	Clear
Adhesive	Clear Permanent Solvent (50g/m ² +/- 5g/m ²)
• Peel Strength	(20 min. DT) 1.437 kgf • (24 hr. DT) 2.115 kgf
• Release Force	50-150 g/50mm
Liner	One-Side Siliconized PET Film - 0.3mm
Film Thickness	24 mil (600µ +/-10µ)
FR Certification	Not Tested
Slip Resistance	ANSI A137.1/A326.3

DURABILITY

Exterior	Up to 3 Years Dependent Upon Mechanical Use of the Surface to Which Applied
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 75°F (+ 15°C to +24°C) and Relative Humidity Between 50% and 55%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (+10°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removal Temp	+50°F (+10°C) or Greater
Laminating Method	Cold

CHEMICAL RESISTANCE

Non-continuous Immersion	Water	50% Anti-freeze in Water
	Bleach	Mineral Spirits
	1% Sodium Hydroxide Gasoline unleaded	Isopropyl Alcohol
Intermittent Exposure Only	25% Sulphuric Acid	
These Are Not Recommended	Trichloroethylene	

*Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. Printed material must be completely dry and/or off-gassed prior to lamination. For best results, use as little laminator tension possible to avoid stretching.

For critical substrates and all surfaces, please test PRIOR to application.

Remarks: The specifications presented above are the average data summarized by PRECEDE under the latest test results. The tolerance has shown to be +/- 5%.



Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex



Material Sizes

- 54" x 50'



Advantages

- Super-Duty Laminate Is Ideal for Demanding Floor and Wall Applications
- Very Robust Construction - Withstands a Wide Variety of Traffic Over Medium- to Long-Term Installation
- Highly Slip Resistant



For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

704-872-2216 • www.cgxusa.com