



## panoRama Cast 1530C, 1540C

A premium exterior mount perforated cast vinyl one-way vision film for long-term applications.

Cast construction is ideal for the most demanding applications where durability & longevity are a priority.

Available in 70/30 and 60/40 film ratios.

### APPLICATIONS

- Transit, Vehicle & Fleet Graphics
- Building Wraps
- Long-Term Exterior Applications

# panoRama Cast 1530C, 1540C

## MATERIAL

Face Film	Printable White Perforated Cast PVC
Back Side	Black for Maximum Contrast
Adhesive	Semi-Permanent Clear Solvent Acrylic
Liner	Siliconized Paper Liner 5.3mil (135µ +/-10µ)
Film Thickness	4.7 mil (120µ +/-5µ)
FR Certification	Testing In-Process- ASTM E84
Recyclable	No

## DURABILITY

Exterior	Up to 7 Years - Vertical Exposure under North American Midwestern Conditions.
Environment	Humidity and Solvent Resistance - Good
Shelf Life	2 Years with Proper Storage
Storage Requirements	Stored at +68°F to +78°F (+10°C to +24°C) with a Relative Humidity between 45% to 55%
Repositionable	No

## APPLICATION/REMOVAL

Application Temp	Minimum +50°F (-4°C)
Service Temp	-50°F + 225°F (-17°C to +121°C)
Removability	Clean Removal with No Adhesive Residue, up to 6 Months. Adhesion May Increase Over Time.
Exclusions	NOT to be Applied to Fresh Paint, Polycarbonate and some PVC (No Exhaustive List Available)

Smooth surface must be clean and dry. Prevent contact with solvents or ammonia-based cleaners. For best results, clean installation surface with soap and water ONLY. Rinse with water and dry after cleaning. ALWAYS clean and dry glass surface prior to applications. For full installation and removal recommendations, please refer to "panoRama Cast 1530, 1540 Exterior Mount Self-Adhesive Perforated Film Handling Recommendations."

\*For critical substrates and all surfaces, please test PRIOR to application.



## Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex
- Screen Print
- Offset



## Material Sizes

- 54" x 82'
- 54" x 164'
- 60" x 164'



## Advantages

- Premium Cast Construction Offers Conformability and the Longest-Term Durability Available without Lamination
- Excellent Dimensional Stability and Strength
- Excellent Removability after Long-Term Installation
- Laminate with Optically Clear panoRama Cast Laminate for Additional Weather and UV Resistance

## → For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

**1-704-872-2216 • [www.cgxusa.com](http://www.cgxusa.com)**

[www.cgxusa.com](http://www.cgxusa.com)

**CONTINENTAL**  
GRAFIX