



Edge Protection Tape

Optically clear, cast PVC film designed to seal the seams and edges of perforated film and other graphic installations.

Protect and prolong the life of films by protecting edges from environmental conditions.

Reinforces the bond between the graphic and substrate in areas prone to weakness, like sharp edges or intricate designs, for a professional finish.

APPLICATIONS

- Transit, Vehicle, and Fleet Graphics
- Perforated Window Graphics
- Long-Term Outdoor Signage

Edge Protection Tape

MATERIAL

Face Film	Optically Clear Cast PVC with a Gloss Finish
Back Side	Clear Adhesive
Adhesive	Permanent Solvent
Liner	PET - 1.5 mil (38μ +/- 5μ)
Film Thickness	2 mil (190μ +/- 5μ)
FR Certification	Testing in Progress
Recyclable	No

DURABILITY

Exterior	Up to 10 Years - Vertical Exposure under North American Midwestern Conditions
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	2 Years with Proper Storage
Storage Requirements	Store at +68°F to +78°F (+10°C to +24°C) and Relative Humidity Between 45% and 55%
Repositionable	No

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (-4°C)
Service Temp	-50°F to +225°F (-17°C to +121°C)
Removability	N/A

Surface must be clean and dry. Handle film with care to prevent damage, fingerprints, debris, and contaminants that could become apparent on the finished product. Prevent contact with solvents or ammonia-based cleaners. For best results, clean final installation surface with soap and water ONLY. Rinse with water and dry after cleaning. ALWAYS clean and dry glass surface prior application.

*For critical substrates and all surfaces, please test PRIOR to application.



Printing Methods

- Not Used for Printing



Material Sizes

- 0.5" x 82'



Advantages

- Protects Window Graphic Edges from Moisture, Dirt and Debris That Causes Premature Peeling or Degrading
- Protects Edges of Window Graphics from Wind, UV Rays and Temperature Fluctuations to Prevent Peeling and Curling
- Provides a Clean, Finished Look to Graphic Installations

→ For more information

For additional product information, performance, and warranty guidelines please contact Continental Graftix USA, Inc.

704-872-2216 • www.cgxusa.com