



panoRama TwoWay Vision

Don't let your branding to get lost in the dark!

Specially engineered translucent PVC film designed to deliver vibrant window graphics visible on both sides of the glass both day and night.

Efficient solution from production to installation - no need for white ink and air egress release liner.

APPLICATIONS

- Retail Store Fronts
- Corporate
 Environments
- Restaurants
- Flat and Slightly Curved Glass

panoRama TwoWay Vision

MATERIAL	
Face Film	Printable Translucent Calendared PVC
Back Side	Translucent
Adhesive	Removable Clear Solvent Acrylic
Liner	Textured Siliconized Paper – 3.3 mil (85µ +/-10µ)
Film Thickness	5 mil (120 μ +/-10 μ)
FR Certification	Not Tested

DURABILITY	
Interior	Up to 3 Years
Exterior	Up to 2 Years - Vertical Exposure under Normal Conditions
Environment	Humidity & Solvent Resistance – Very Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 77°F (+15°C to +25°C) and Relative Humidity between 45% to 75%
Repositionable	Yes – During Initial Installation

APPLICATION/REMOVAL		
Application Temp	+50°F to +86°F (+10°C to +30°C)	
Service Temp	-14°F to +122°F (-25°C to +50°C)	
Removability	Clean Removal with No Adhesive Residue, up to 6 Months - Adhesion May Increase over Time	
Removal Temp	+50°F (+10°C) or Greater	
Exclusions	NOT to Be Applied to Fresh Paint, Polycarbonate, and Some PVC (No Exhaustive List Available)	

Surface must be clean and dry. Prevent contact with solvent or ammoniabased cleaners. For best results, clean glass or install surface with a mild detergent and water and dry thoroughly prior to application. ALWAYS clean and dry glass surface prior to application.

*For critical substrates and all surfaces, please test PRIOR to application. Rev 7/2025





Printing Methods

 Digital - Solvent, Eco-Solvent, UV, & Latex



Material Sizes

• 54" x 100'



Advantages

- Transmits Ambient Light for Vibrant Translucent Window Graphics Both Day and Night
- · No White Ink Needed
- Ease of Installation with Air Egress Liner
- Clean Removability (Up to 6 Months Without Residue)



For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

1-704-872-2216 · www.cgxusa.com

