



FatFloor/ White DoubleStick

Clear textured printable PVC designed for medium- to long-term floor and wall applications. Provides affordable, enduring protection for wall and floor graphics in high-traffic areas.

White DoubleStick is a double-sided mounting adhesive for use in place of the white ink layer needed for FatFloor or to add adhesive in place of carpet tape.

APPLICATIONS

- Retail Entrances
- Museum Exhibits
- High-Traffic Event Graphics
- Showroom
- Counter Mats

FatFloor/White DoubleStick

MATERIAL • FAT FLOOR

Face Film	Textured, Transparent PVC Film
Back Side	Clear
Adhesive	None
Liner	None
Film Thickness	55 mil (1400µ +/-10µ)
FR Certification	ASTM D2859
Slip Resistance	ANSI A137.1/A326.3, R10

MATERIAL • WHITE DOUBLESTICK

Description	White Double-Sided Mounting Adhesive
Carrier Film	White Gloss Calendered PVC
Adhesive	Clear Semi-Permanent Solvent, Designed Especially for Smooth Surfaces - 1 mil (25µ +/- 10µ), Each Side
Liner	Siliconized Paper - 100 gsm
Film Thickness	3 mil (70µ +/-10µ)
Repositionable	Yes

DURABILITY

Exterior	Up to 3 Years Dependent Upon Mechanical Use of the Surface to Which Applied
Environment	Humidity & Solvent Resistance - Very Good
Shelf Life	1 Year
Storage Requirements	Store at 59°F to 75°F (+ 15°C to +24°C) and Relative Humidity Between 50 and 55%
Repositionable	Yes

APPLICATION/REMOVAL

Application Temp	Minimum +50°F (+10°C)
Service Temp	+0°F to +122°F (-17°C to +50°C)
Removal Temp	+50°F (+10°C) or Greater
Exclusions	Not Suitable for Polished Stone

CHEMICAL RESISTANCE

Non-continuous Immersion	<ul style="list-style-type: none"> • Water • Bleach • 1% Sodium Hydroxide • Diesel Fuel/ Unleaded Gasoline 	<ul style="list-style-type: none"> • 50% Anti-freeze in Water • Mineral Spirits • Isopropyl Alcohol • 10% Salt Water
Intermittent Exposure Only	<ul style="list-style-type: none"> • 25% Sulphuric Acid 	
These Are Not Recommended	<ul style="list-style-type: none"> • Trichloroethylene • Methyl Ethyl Ketone 	

**Color and lot variances of coated surfaces including paints, power coatings, lacquers, stains, and other treatments may vary the performance, and should be evaluated for compatibility prior to use. For critical substrates and all surfaces, please test PRIOR to application.*

Rev 2/2026

www.cgxusa.com



Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex*

**Latex printable on XXL machines only.*



Material Sizes

- 54" x 50'



Advantages

- No Adhesive - Simple Application and Removal. Use Clear Carpet Tape When Minimal Tack Is Desired
- Very Robust Construction - Withstands Pedestrian and Auto Traffic
- Use White DoubleStick When White Ink Is Not Available and/or Full Adhesive Tack Is Desired



For more information

For additional product information, performance, and warranty guidelines please contact Continental Gratrix USA, Inc.

704-872-2216 • www.cgxusa.com

CONTINENTAL
GRAFIX