



## X-Treme Air

A 6 mil smooth, white vinyl film backed with a proprietary removable adhesive and air egress liner for easy installation.

Uses trusted Walk&Wall® specially-formulated high tack removable (HTR) adhesive for installation in extreme temperature conditions and well suited for low surface energy substrates.

Ideal for businesses with multiple locations & different or unknown wall materials in each location.

### APPLICATIONS

- Wall Graphics
- Retail Graphics POP & Packages
- Labels & Stickers
- Glass, Wood, Metal, Concrete, Low Surface Energy Substrates

# X-Treme Air

## MATERIAL

Face Film	Printable White Smooth PVC
Back Side	White
Adhesive	Proprietary Removable Semi-Permanent
Liner	Siliconized Paper Liner – 5 mil (130µ +/-10µ)
Film Thickness	6 mil (1520µ +/-10µ)
FR Certification	In-Process

## DURABILITY

Interior	Up to 5 Years
Exterior	Up to 5 Years Vertical Exposure under Normal Conditions
Environment	Humidity & Solvent Resistance – Very Good
Shelf Life	1 Year
Storage Requirements	Stored at 59°F to 77°F (+15°C to +25°C) with a Relative Humidity between 45% to 70%
Repositionable	Yes – During Initial Installation

## APPLICATION/REMOVAL

Application Temp On Trailers	+5°F to +122°F (-15°C to +50°C) +50° to +122°F (+10°C to +50°C)
Service Temp	-13°F to +158°F (-25°C to +70°C)
Removability	Clean Removal with No Adhesive Residue, up to 6 Months – Adhesion May Increase over Time
Removal Temp	+50°F (+10°C) to +95°F (+35°C)
Exclusions	NOT to Be Applied to Fresh Paint or Ink, Polycarbonate, and Some PVC (No Exhaustive List Available)

Surface must be clean and dry. Prevent contact with solvent or ammonia-based cleaners. For best results, clean surfaces with a mild detergent and water and dry thoroughly. Always clean and dry glass and surfaces prior to application. For full installation and removal recommendations, please refer to X-Treme Air Handling Instructions

\*For critical substrates and all surfaces, please test PRIOR to application.

Rev 3/2026

[www.cgxusa.com](http://www.cgxusa.com)



## Printing Methods

- Digital - Solvent, Eco-Solvent, UV, & Latex
- Screen Print
- Offset



## Material Sizes

- 54" x 164'



## Advantages

- Excellent Temperature Resistance and Dimensional Stability
- Application in Extreme Cold and Heat, Low Surface Energy Substrates
- Easy to Install for Retail Graphics Packages and POP

## → For more information

For additional product information, performance, and warranty guidelines please contact Continental Grafix USA, Inc.

**1-704-872-2216 • [www.cgxusa.com](http://www.cgxusa.com)**

CONTINENTAL  
GRAFIX